

A25 series air quality meters are used to measure PM2.5 concentration. A25 series can be used in homes, offices, hotels, schools, factories, hospitals, restaurants, and other public places.

### Features

Precise PM2.5 concentration based on pre-calibrated sensors

Temperature measurement (°C/°F)

Humidity measurement (A25D)

Emoticon display

LCD backlight and red backlight alarm

Battery status, auto power off



A25M



A25D

Specifications	Range	A25M	A25D
<b>Certificates</b>	<b>CE, UKCA</b>		
PM2.5 (ug/m <sup>3</sup> )	0~100	±(10ug/m <sup>3</sup> +10dgts)	±(10ug/m <sup>3</sup> +10dgts)
	101~400	±(10%+30dgts)	±(10%+30dgts)
	401~500	±(10%+50dgts)	±(10%+50dgts)
Formaldehyde (mg/m <sup>3</sup> )	0~2		
Temperature	-10°C~50°C	For reference only	±1°C
Humidity	5%~99%RH		±5%RH@30%~80%RH
			±8%RH@<30%RH, >80%RH

### Characteristics

Standard accessories	1m micro USB cable, wall mount (A25M), English manual
Power	A25M: 520mAh Li-ion battery; A25D: 1500mAh Li-ion battery
Display	A25M: 35 x 35mm; A25D: 42 x 65mm
Product size	A25M: 64 x 60 x 28mm; A25D: 75 x 55 x 130mm
Product net weight	A25M: 85g; A25D: 230g
Standard individual packing	Gift box
Standard quantity per carton	A25M: 20pcs; A25D: 5pcs
Standard carton measurement	A25M: 325 x 215 x 210mm; A25D: 360 x 185 x 140mm
Standard carton gross weight	A25M: 4.5kg; A25D: 2.35kg